

# MATERIAL SAFETY DATA SHEET (MSDS)

## SUREMIX

(Please ensure that this MSDS is received by the appropriate person)

Ref. no.: MS059                      DATE: December 2015

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT IDENTIFICATION

Product Name	SUREMIX
Chemical Formula	CO <sub>2</sub> N <sub>2</sub> CO <sub>2</sub> plus N <sub>2</sub>
Trade Names	Suremix N Suremix 30 Suremix 50 Suremix 60 Suremix 100
Colour coding	Suremix N Ivory body with a French Grey (H30) shoulder. The relevant grade is stencilled on the cylinder. Suremix 30 – Ivory body with a Brunswick green (H07) shoulder. The relevant grade is stencilled on the cylinder. Suremix 60 – Ivory body with a Purple shoulder. The relevant grade is stencilled on the cylinder. Suremix 100 – Ivory body with the grade stencilled on the cylinder.
Valves	Suremix N – Brass ¾ inch BSP right hand female. Suremix 30,50 and 60 – Brass 5/8 inch BSP, right hand female. Suremix 100 – Brass 0,860 inch by 14 tpi right hand male.
Company Identification	African Oxygen Limited 23 Webber Street Johannesburg, 2001 Tel. No: (011) 490-0400 Fax No: (011) 490-0506
<b>EMERGENCY No</b>	<b>0860020202 (24 hr)</b>

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Names	Carbon dioxide Nitrogen
	<b><u>Carbon Dioxide</u></b> <b><u>Nitrogen</u></b>
Cas Nos.	124-38-9                                      7727-37-9
UN Nos.	1013    1066
	<b><u>Carbon Dioxide /Nitrogen Mixtures</u></b>
UN Nos.	1956
ERG No	121
Hazchem Warning	2 C Non-flammable gas

### 3 HAZARDS IDENTIFICATION

**Main Hazards** All cylinders are portable gas containers and must be regarded as pressure vessels at all times. The various grades of Suremix do not support life. They can act as simple asphyxiants by diluting the concentration of oxygen in air below the levels necessary to support life. Excepting for Suremix N, they are all heavier than air and will tend to concentrate at lower levels.

**Adverse Health effects** The carbon dioxide component contained in the relevant grades of Suremix acts as a stimulant and a depressant on the central nervous system. Increases in heart rate and blood pressure have been noted at a concentration of 7.6 percent, and dyspnea (laboured breathing), headache, dizziness and sweating occur if exposure at that level is prolonged. In the case of Suremix N, the inhalation of nitrogen in excessive concentrations can result in dizziness, nausea, vomiting, loss of consciousness and death.

**Chemical hazards** Both the carbon dioxide and nitrogen components of the listed grades of Suremix are

non-toxic. They will not burn or support combustion.

**Biological hazards** The greatest physiological effect of carbon dioxide is to stimulate the respiratory centre, thereby controlling the volume and rate of respiration. It is able to cause dilation and constriction of blood vessels and is a vital constituent of the acid-base mechanism that controls the pH of the blood.

**Vapour inhalation** At concentrations of 10 percent of carbon dioxide and above, unconsciousness can result in one minute or less. Impairment in performance has been noted during prolonged exposure to concentrations of 3 percent carbon dioxide even when the oxygen concentration was 21 percent. In the case of Suremix N, the nitrogen acts as a simple asphyxiant and death may occur in seconds without warning.

**Eye Contact** No known effect

**Skin Contact** No known effect

**Ingestion** (See "Vapour Inhalation" above)

### 4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to Suremix. Rescue personnel should be equipped with self-contained breathing apparatus. For those grades of Suremix that contains carbon dioxide, concentrations of 10 percent or more can produce unconsciousness or death. Lower concentrations may cause headache, sweating, rapid breathing, increased heartbeat, and shortness of breath, dizziness, mental depression, visual disturbances and shaking. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area and given mouth-to-mouth resuscitation and supplemental oxygen.

**Eye contact** No known effect

**Skin contact** No known effect

**Ingestion** (See section 3 above)

### 5 FIRE FIGHTING MEASURES

**Extinguishing media** All the grades of Suremix are non-flammable and do not support combustion, thus do not contribute to a fire, but could help with the extinguishing by reducing the oxygen content of the air by dilution to below the level to support combustion.

**Specific hazards** Suremix does not support life. They can act as simple asphyxiants by diluting the concentration of oxygen in the air below the levels to support life.

**Emergency actions** If possible, shut off the source of excess Suremix. Evacuate area. All cylinders should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. Cylinders which have been exposed to excessive heat should be clearly identified and returned to the supplier. CONTACT THE NEAREST AFROX BRANCH.

**Protective clothing** Self-contained breathing apparatus. Safety goggles, gloves and shoes, or boots, should be worn when handling cylinders.

**Environmental precautions** Excepting for Suremix N, all the other grades are heavier than air and could accumulate in low-lying areas. Care should be taken when entering a potentially oxygen-deficient environment. If possible, ventilate the affected area. Suremix N is lighter than air and disperses rapidly in the atmosphere. Care should be taken when entering a potentially oxygen-deficient environment. If possible, ventilate the affected area.

## MATERIAL SAFETY DATA SHEET (MSDS)

### SUREMIX

(Please ensure that this MSDS is received by the appropriate person)

#### 6 ACCIDENTAL RELEASE MEASURES

<b>Personal</b>	Do not enter any area where Suremix has been spilled unless tests have shown that it is safe to do so.
<b>Precautions</b>	
<b>Environmental precautions</b>	Suremix does not pose a hazard to the environment.
<b>Small spills</b>	Shut off the source of the escaping Suremix. Ventilate the area.
<b>Large spills</b>	Evacuate the area. Shut off the source of the spill if this can be done without risk. Restrict access to the area until completion of the clean-up procedure. Ventilate the area using forced draught if necessary.

#### 7 HANDLING AND STORAGE

Do not allow cylinders to slide or come into contact with sharp edges. Excepting for Suremix 100, which should be stacked vertically, all other grades may be stacked horizontally provided that they are firmly secured at each end to prevent rolling. Use a "first in - first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational exposure hazards</b>	As Suremix is a simple asphyxiant, avoid any areas where spillage has taken place
<b>Engineering control measures</b>	Engineering control measures are preferred to reduce exposures to oxygen depleted atmospheres. General methods include forced-draught ventilation, separate from other exhaust ventilation systems.
<b>Personal protection</b>	Self-contained breathing apparatus should always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders.
<b>Skin</b>	No known effect.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

##### PHYSICAL DATA

<b>Carbon Dioxide</b>	
Chemical Symbol	CO <sub>2</sub>
Molecular Weight	44,01
Specific volume @ 20°C & 101,325 kPa	547 ml/g
Relative density of gas @ 101,325 kPa (Air = 1)	1,53
Colour	None
Taste	Acidic
Odour	None
<b>Nitrogen</b>	
Chemical Symbol	N <sub>2</sub>
Molecular Weight	28,013
Specific volume @ 20°C & 101,325 kPa	861,5 ml/g
Relative density of gas @ 101,325 kPa (Air = 1)	0,967
Colour	None
Taste	None
Odour	None

#### 10 STABILITY AND REACTIVITY

**Conditions to avoid** The dilution of oxygen in the atmosphere to levels which cannot support life. Never use cylinders as rollers or supports, or for any other purpose than the storing of Suremix. Never expose cylinders to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.

**Incompatible materials.** As dry Suremixers are inert, they may be contained in systems constructed of any of the common metals which have been designed to safely withstand the pressures involved.

**Hazardous Decomposition Products** None

#### 11 TOXICOLOGICAL INFORMATION

Acute Toxicity	TLV 5000 vpm (for CO <sub>2</sub> )
Skin & eye contact	No known effect
Chronic Toxicity	No known effect
Carcinogenicity	No known effect
Mutagenicity	No known effect
Reproductive Hazards	No known effect

(For further information see Section 3. Adverse health effects)

#### 12 ECOLOGICAL INFORMATION

Those Suremixes containing carbon dioxide are heavier than air and can cause pockets of oxygen-depleted atmosphere in low-lying areas. They do not pose a hazard to the ecology.

#### 13 DISPOSAL CONSIDERATIONS

<b>Disposal Methods</b>	Small amounts may be blown to the atmosphere under controlled conditions. Large amounts should only be handled by the gas supplier.
<b>Disposal of Packaging</b>	The disposal of containers must only be handled by the gas supplier.

#### 14 TRANSPORT INFORMATION

##### ROAD TRANSPORTATION

UN No.	1956
ERG No	121
Hazchem warning	2C Non-flammable gas

##### SEA TRANSPORTATION

IMDG	1956
Class	2.2
Label	Non-flammable gas

##### AIR TRANSPORTATION

ICAO/IATA Code	1956
Class	2.2

##### Packaging instructions

- Cargo	200
- Passenger	200
Maximum quantity allowed	
- Cargo	150 kg
- Passenger	75 kg

#### 15 REGULATORY INFORMATION

EEC Hazard class	Non-flammable
National legislation	OHSact and Regulations 85 of 1993
SABS 10234 and its supplement for explanation of the above.	

#### 16 OTHER INFORMATION

**Bibliography**  
Compressed Gas Association, Arlington, Virginia  
Handbook of Compressed Gases - 3<sup>rd</sup> Edition  
Matheson. Matheson Gas Data Book - 6<sup>th</sup> Edition  
SABS 0265 - Labelling of Dangerous Substances

#### 17 EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.

## MATERIAL SAFETY DATA SHEET (MSDS)

### SUREMIX

**(Please ensure that this MSDS is received by the appropriate person)**

---

AFROX a member of The LINDE Group

The Stripe Symbol and the word AFROX are AFROX Group Trademarks.

For product and safety enquiries please phone

**EMERGENCY N°:**  
**0860020202 (24 hr)**